


Dimensions et poids de coude 90-deg 1.5D LR à souder bout à bout ASME B16.9

LE RACCORDEMENT



Size(NPS)	OD	A	Epaisseur T et Poids					T (mm)
			Sch 10s	Sch 40s	Sch STD	Sch 80s	Sch XS	Poids (Kg)
1/2	21.3	38	2.11	2.77	2.77	3.73	3.73	
			0.06	0.08	0.08	0.10	0.10	
3/4	26.7	38	2.11	2.87	2.87	3.91	3.91	
			0.08	0.10	0.10	0.13	0.13	
1	33.4	38	2.77	3.38	3.38	4.55	4.55	
			0.13	0.15	0.15	0.19	0.19	
1 1/4	42.2	48	2.77	3.56	3.56	4.85	4.85	
			0.20	0.26	0.26	0.35	0.35	
1 1/2	48.3	57	2.77	3.68	3.68	5.08	5.08	
			0.28	0.37	0.37	0.48	0.48	
2	60.3	76	2.77	3.91	3.91	5.54	5.54	
			0.47	0.66	0.66	0.90	0.90	
2 1/2	73.0	95	3.05	5.16	5.16	7.01	7.01	
			0.83	1.31	1.31	1.80	1.80	
3	88.9	114	3.05	5.49	5.49	7.62	7.62	
			1.17	2.06	2.06	2.86	2.86	
4	114.3	152	3.05	6.02	6.02	8.56	8.56	
			2.03	3.76	3.76	5.46	5.46	
5	141.3	190	3.40	6.55	6.55	9.53	9.53	
			3.41	6.47	6.47	9.14	9.14	
6	168.3	229	3.40	7.11	7.11	10.97	10.97	
			4.96	10.10	10.10	15.40	15.40	
8	219.1	305	3.76	8.18	8.18	12.70	12.70	
			9.65	20.40	20.40	31.00	31.00	
10	273.0	381	3.40	9.27	9.27	12.70	12.70	
			16.70	36.20	36.20	57.60	48.80	
12	323.8	457	3.96	9.53	9.53	12.70	12.70	
			26.10	55.50	52.80	95.20	70.40	

- Dimensions en mm