


Dimensions et poids de caps à souder bout à bout ASME B16.9



Size(NPS)	OD	E	Ep. Limite pour E	E1	Epaisseur T et Poids				
					T (mm)				
					Poids (Kg)				
					Sch 10s	Sch 40s	Sch STD	Sch 80s	Sch XS
1/2	21.3	25	4.57	25	2.11	2.77	2.77	3.73	3.73
					0.03	0.04	0.04	0.05	0.05
3/4	26.7	25	3.81	25	2.11	2.87	2.87	3.91	3.91
					0.04	0.05	0.05	0.07	0.07
1	33.4	38	4.57	38	2.77	3.38	3.38	4.55	4.55
					0.09	0.11	0.11	0.14	0.14
1 1/4	42.2	38	4.83	38	2.77	3.56	3.56	4.85	4.85
					0.11	0.14	0.14	0.19	0.19
1 1/2	48.3	38	5.08	38	2.77	3.68	3.68	5.08	5.08
					0.13	0.17	0.17	0.24	0.24
2	60.3	38	5.59	44	2.77	3.91	3.91	5.54	5.54
					0.17	0.24	0.24	0.33	0.33
2 1/2	73.0	38	7.11	51	3.05	5.16	5.16	7.01	7.01
					0.23	0.39	0.39	0.53	0.53
3	88.9	51	7.62	64	3.05	5.49	5.49	7.62	7.62
					0.37	0.66	0.66	0.92	0.92
4	114.3	64	8.64	76	3.05	6.02	6.02	8.56	8.56
					0.59	1.17	1.17	1.67	1.67
5	141.3	76	9.65	89	3.40	6.55	6.55	9.53	9.53
					1.00	1.93	1.93	2.81	2.81
6	168.3	89	10.92	102	3.40	7.11	7.11	10.97	10.97
					1.39	2.90	2.90	4.47	4.47
8	219.1	102	12.70	127	3.76	8.18	8.18	12.70	12.70
					2.38	2.19	2.19	8.05	8.05

- Dimensions en mm